

Humminbird 998 Si Specs

| | |
|---|---|
| Display Size: | 8.0" diagonal |
| Display Pixel Matrix: | 480V x 800H |
| Display Type: | 16:9 Color TFT |
| Display Colors/Grayscale: | 65,000 Colors |
| DualBeam PLUS | |
| Sonar Coverage | <ul style="list-style-type: none">• 200 kHz / 20° @ -10db• 83 kHz / 60° @ -10db |
| HD Side Imaging & Down Imaging | |
| Sonar Coverage | <ul style="list-style-type: none">• 455 kHz / (2) 86° @ -10db• 800 kHz / (2) 55° @ -10db |
| Sonar Optional: | QuadraBeam PLUS |
| Target Separation: | 2.5 inches |
| Power Output (RMS): | 1000 Watts (RMS) |
| Power Output (Peak to Peak): | 8000 Watts (Peak-to-Peak) |
| Temperature: | Included |
| Speed: | GPS Speed Included |
| Backlight: | Yes |
| Waterproof: | Yes |
| Mount: | Gimbal |
| Unit Size: | 11" W x 6" H x 4" D |
| Mount: | In-dash |
| Unit Size: | 11" W x 6" H x 2" D |
| Transducer – Standard: | XHS-9-HDSI-180-T |
| Transducer Mounting: | Transom |
| Power Input: | 10-20 VDC |